

Product description

an one component alkyd paint contains zinc chromate inhibitive pigment which protects to structural steel which will be subjected to general atmospheric conditions. Recommended with proper primer for surfaces exposed to weather middle, atmospheric corrosion, moisture air.

Product advantage

- good weathering resistance
- excellent easy apply
- good resistance against corrosion
- resistance against sunlight and acid rain

color	components	expiry date	pack size
green	1	12 months	4L&20L

Surface preparation

Steel surfaces: must be clean and dry. Remove water, dirt, dust, oil and grease. Removed dust by using power tools or sanding.

Paint preparation

stir paint thoroughly.
Use Rtc.15 thinner for thinning.

Thinner code Rtc.15
Paint series R15.

Application

method	Line pressure	Tip size	Fan angle
Air spray	3-5 bar	1.2-2.5mmC	40-80°
Brush & roller			

surface temperature	paint temperature	temperature	humidity
3°C > dew point	4°C > surfaces temperature	10-45 °C	<85%

Temperature	touch dry	hard dry	Recoat
25°C	12 hrs.	16 hrs	16 hrs. (Min.)

Storage

Store in cool and dry conditions. (Between 5-30 °C)

These products are flammable; keep away from direct heat source and sunlight.

Keep container away from moisture.

Use these products before expiry date.

When not using the material always replace the lid on the container.

Health and safety resolution

avoid breathing vapor.

vapor masks should be worn for application

protective gloves should be worn

ensure adequate, constant fresh air ventilation during and after use

avoid prolonged contact with skin-in case of contact with mouth or nose, wash with water and obtain medical attention.

If splashed into the eyes, flush them with copious quantities of clean water for 10 minutes and get urgent medical attention.